



## EverGuard® TPO QuickSpray Adhesive



### Description:

EverGuard® TPO Quick Spray Adhesive is a sprayable, solvent-based contact adhesive useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

### Features and Benefits:

- Faster installation than traditional bonding adhesive
- High initial tack
- Shelf life-2 years from the date of manufacture

### Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- For TPO membrane, spraying from 8" - 12" (203 mm - 305 mm) away, apply adhesive uniformly to both the substrate and the membrane underside
- As primer for SA Vapor Retarder, apply to the substrate only
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply at an ambient temperature of 20°F (-6.7°C) and above. The cylinders must be kept above 50°F (10°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C).
- Apply pressure with a push broom or weighted roller to ensure complete bonding
- To clean Hose & Gun Kit, attach hose and gun to EverGuard® Quick Spray or EverGuard® Quick Spray LV50 Cleaning Kit and run cleaner through hose and gun for approximately 10 - 15 seconds. Each cleaner canister should get approximately 9 - 10 cleanings for the 10 square size.

### Product Details:

#### EverGuard® TPO Quick Spray Adhesive

- SKU 7806 - 3 squares - 13.65 lb. (6.2 kg)
- SKU 7792 - 10 squares - 40.15 lb. (18.2 kg)
- VOC: 489 g/L
- Installation Temperature: 20°F (-6.7°C) and rising
- Cleaner SKU: 7802
- Hose & Gun SKU: 7804 or 7805
- Hose Splitter: 7826
- 25' Hose: 7825

Coverage rates and flash time may vary in colder temperatures.

### Codes & Standards:

- **UL Classified:** Refer to UL Online Certification Directory for actual assemblies.



- **State of Florida Approved**



Visit [gaf.com/QuickSpray](https://www.gaf.com/QuickSpray)

For additional information, contact Design Services at 1-877-423-7663 or [designservices@gaf.com](mailto:designservices@gaf.com)

We protect what matters most™

